

STAW

STRAIGHT ARROW (White)

RTAW

RIGHT TURN ARROW (White)

LTAW

LEFT TURN ARROW (White)

Layouts shown are for typical installations. Drawings are oriented to represent direction of traffic moving from left to right.

Center markings within the lane.

All dimensions shown are nominal. For proper proportion details, see current MUTCD Standard Highway Signs and Markings booklet.

Pavement word, symbol, and arrow markings are to be proportionally scaled to fit within the width of the facility upon which they are applied.

CSRW

COMBINED STRAIGHT AND RIGHT TURN ARROW (White)

CSLW

COMBINED STRAIGHT AND LEFT TURN ARROW (White)

CSTW

COMBINED STRAIGHT, RIGHT AND LEFT TURN ARROW (White)

Except for the SCHOOL word marking, all markings are to be no more than one lane in width.

① Add template for Right Turn Arrow (RTAW) to Left Turn Arrow (LTAW) or Combined Straight and Left Turn Arrow (CSLW) to create new templates.

CRLW

COMBINED RIGHT AND LEFT TURN ARROW (White)

FERW

FREEWAY, EXPRESSWAY AND RAMP ARROW (White)

LLRW

LEFT LANE REDUCTION ARROW (White)

Possible Contract Item:
Pavement Marking Symbols and
Legends Items

Possible Tabulation:
108-29

RLRW

RIGHT LANE REDUCTION ARROW (White)

RRCW

RAILROAD CROSSING SYMBOL (White)

IOWA DOT

STANDARD ROAD PLAN

REVISIONS: Added SLSW.

APPROVED BY DESIGN METHODS ENGINEER

REVISION

4 04-21-20

PM-111

SHEET 1 of 2

SYMBOLS AND LEGENDS

BLSW

BIKE LANE SYMBOL (White)

Diagram of the Bike Lane Symbol (White) showing dimensions: 72" wide and 40" high.

WCSW

WHEELCHAIR SYMBOL (White)

Diagram of the Wheelchair Symbol (White) showing dimensions: 7'-0" wide and 6'-6" high.

WPSB

WHEELCHAIR PARKING SYMBOL (Blue)

Diagram of the Wheelchair Parking Symbol (Blue) showing dimensions: 28" wide and 24" high.

② When placed across one lane, use the smaller dimensions shown. When placed across two lanes, use the larger dimensions shown.

SCLW

SCHOOL WORD MARKING (White)

Diagram of the School Word Marking (White) showing dimensions: 8'-0" or 10'-0" wide and 9'-3" or 19'-4" high.

XNGW

XING WORD MARKING (White)

Diagram of the Xing Word Marking (White) showing dimensions: 8'-0" wide and 5'-1" high.

STPW

STOP WORD MARKING (White)

Diagram of the Stop Word Marking (White) showing dimensions: 8'-0" wide and 7'-8" high.

AHDW

AHEAD WORD MARKING (White)

Diagram of the Ahead Word Marking (White) showing dimensions: 8'-0" wide and 10'-8" high.

ONLW

ONLY WORD MARKING (White)

Diagram of the Only Word Marking (White) showing dimensions: 8'-0" wide and 5'-9" high.

XITW

EXIT WORD MARKING (White)

Diagram of the Exit Word Marking (White) showing dimensions: 8'-0" wide and 6'-0" high.

BIKW

BIKE WORD MARKING (White)

Diagram of the Bike Word Marking (White) showing dimensions: 44" wide and 32" high.

LANW

LANE WORD MARKING (White)

Diagram of the Lane Word Marking (White) showing dimensions: 44" wide and 32" high.

SLSW

SHARED LANE SYMBOL (White)

Diagram of the Shared Lane Symbol (White) showing dimensions: 72" wide for the bike symbol and 40" high for the arrow, with a total width of 112" for the combined symbol.

STANDARD ROAD PLAN

REVISIONS: Added SLSW.

APPROVED BY DESIGN METHODS ENGINEER

REVISION

404-21-20

PM-111

SHEET 2 of 2

SYMBOLS AND LEGENDS