



Triple Reinforced Concrete Box Culvert Standards

Index for Triple Culvert Standards:

TRRCB G1-20	Index of Sheets
TRRCB G2-20	General Notes & Specifications
TRRCB G3-20	Typical Culvert Barrel Details
TRRCB 10-4-20	Culvert Barrel Details, 10' x 4' Barrel Sections
TRRCB 10-5-20	Culvert Barrel Details, 10' x 5' Barrel Sections
TRRCB 10-6-20	Culvert Barrel Details, 10' x 6' Barrel Sections
TRRCB 10-7-20	Culvert Barrel Details, 10' x 7' Barrel Sections, Sheet 1 of 2
TRRCB 10-7-20	Culvert Barrel Details, 10' x 7' Barrel Sections, Sheet 2 of 2
TRRCB 10-8-20	Culvert Barrel Details, 10' x 8' Barrel Sections, Sheet 1 of 2
TRRCB 10-8-20	Culvert Barrel Details, 10' x 8' Barrel Sections, Sheet 2 of 2
TRRCB 10-9-20	Culvert Barrel Details, 10' x 9' Barrel Sections, Sheet 1 of 2
TRRCB 10-9-20	Culvert Barrel Details, 10' x 9' Barrel Sections, Sheet 2 of 2
TRRCB 10-10-20	Culvert Barrel Details, 10' x 10' Barrel Sections, Sheet 1 of 2
TRRCB 10-10-20	Culvert Barrel Details, 10' x 10' Barrel Sections, Sheet 2 of 2
TRRCB 10-11-20	Culvert Barrel Details, 10' x 11' Barrel Sections, Sheet 1 of 2
TRRCB 10-11-20	Culvert Barrel Details, 10' x 11' Barrel Sections, Sheet 2 of 2
TRRCB 10-12-20	Culvert Barrel Details, 10' x 12' Barrel Sections, Sheet 1 of 2
TRRCB 10-12-20	Culvert Barrel Details, 10' x 12' Barrel Sections, Sheet 2 of 2
TRRCB 12-4-20	Culvert Barrel Details, 12' x 4' Barrel Sections
TRRCB 12-5-20	Culvert Barrel Details, 12' x 5' Barrel Sections
TRRCB 12-6-20	Culvert Barrel Details, 12' x 6' Barrel Sections
TRRCB 12-7-20	Culvert Barrel Details, 12' x 7' Barrel Sections, Sheet 1 of 2
TRRCB 12-7-20	Culvert Barrel Details, 12' x 7' Barrel Sections, Sheet 2 of 2
TRRCB 12-8-20	Culvert Barrel Details, 12' x 8' Barrel Sections, Sheet 1 of 2
TRRCB 12-8-20	Culvert Barrel Details, 12' x 8' Barrel Sections, Sheet 2 of 2
TRRCB 12-9-20	Culvert Barrel Details, 12' x 9' Barrel Sections, Sheet 1 of 2
TRRCB 12-9-20	Culvert Barrel Details, 12' x 9' Barrel Sections, Sheet 2 of 2
TRRCB 12-10-20	Culvert Barrel Details, 12' x 10' Barrel Sections, Sheet 1 of 2
TRRCB 12-10-20	Culvert Barrel Details, 12' x 10' Barrel Sections, Sheet 2 of 2
TRRCB 12-11-20	Culvert Barrel Details, 12' x 11' Barrel Sections, Sheet 1 of 2
TRRCB 12-11-20	Culvert Barrel Details, 12' x 11' Barrel Sections, Sheet 2 of 2
TRRCB 12-12-20	Culvert Barrel Details, 12' x 12' Barrel Sections, Sheet 1 of 2
TRRCB 12-12-20	Culvert Barrel Details, 12' x 12' Barrel Sections, Sheet 2 of 2
TRPWH 0-1-20	Parallel Wing Hdwls., 0° Skew, Dimension Table
TRPWH 0-2-20	Parallel Wing Hdwls., 0° Skew, Cross Section Details
TRWPH 0-3-20	Parallel Wing Hdwls., 0° Skew, Wingwall Elev.
TRPWH 0-4-20	Parallel Wing Hdwls., 0° Skew, Bott. Apron Reinf.
TRPWH 0-5-20	Parallel Wing Hdwls., 0° Skew, Top Apron Reinf.
TRPWH 0-6-20	Parallel Wing Hdwls., 0° Skew, Quantity Tabulation, 12'-0" Span, Sheet 1 of 2
TRPWH 0-6-20	Parallel Wing Hdwls., 0° Skew, Quantity Tabulation, 12'-0" Span, Sheet 2 of 2
TRPWH 0-7-20	Parallel Wing Hdwls., 0° Skew, Quantity Tabulation, 10'-0" Span, Sheet 1 of 2
TRPWH 0-7-20	Parallel Wing Hdwls., 0° Skew, Quantity Tabulation, 10'-0" Span, Sheet 2 of 2
TRPWH 15-1-20	Parallel Wing Hdwls., 15° Skew, Dimension Table
TRPWH 15-2-20	Parallel Wing Hdwls., 15° Skew, Cross Section Details
TRPWH 15-3-20	Parallel Wing Hdwls., 15° Skew, Wingwall Elev.
TRPWH 15-4-20	Parallel Wing Hdwls., 15° Skew, Bott. Apron Reinf.
TRPWH 15-5-20	Parallel Wing Hdwls., 15° Skew, Top Apron Reinf.
TRPWH 15-6-20	Parallel Wing Hdwls., 15° Skew, Quantity Tabulation, 12'-0" Span, Sheet 1 of 2
TRPWH 15-6-20	Parallel Wing Hdwls., 15° Skew, Quantity Tabulation, 12'-0" Span, Sheet 2 of 2
TRPWH 15-7-20	Parallel Wing Hdwls., 15° Skew, Quantity Tabulation, 10'-0" Span, Sheet 1 of 2
TRPWH 15-7-20	Parallel Wing Hdwls., 15° Skew, Quantity Tabulation, 10'-0" Span, Sheet 2 of 2
TRPWH 30-1-20	Parallel Wing Hdwls., 30° Skew, Dimension Table
TRPWH 30-2-20	Parallel Wing Hdwls., 30° Skew, Cross Section Details
TRPWH 30-3-20	Parallel Wing Hdwls., 30° Skew, Wingwall Elev.
TRPWH 30-4-20	Parallel Wing Hdwls., 30° Skew, Bott. Apron Reinf.
TRPWH 30-5-20	Parallel Wing Hdwls., 30° Skew, Top Apron Reinf.
TRPWH 30-6-20	Parallel Wing Hdwls., 30° Skew, Quantity Tabulation, 12'-0" Span, Sheet 1 of 2
TRPWH 30-6-20	Parallel Wing Hdwls., 30° Skew, Quantity Tabulation, 12'-0" Span, Sheet 2 of 2
TRPWH 30-7-20	Parallel Wing Hdwls., 30° Skew, Quantity Tabulation, 10'-0" Span, Sheet 1 of 2
TRPWH 30-7-20	Parallel Wing Hdwls., 30° Skew, Quantity Tabulation, 10'-0" Span, Sheet 2 of 2

Index for Triple Culvert Standards (cont'd):

TRPWH 45-1-20	Parallel Wing Hdwls., 45° Skew, Dimension Table
TRPWH 45-2-20	Parallel Wing Hdwls., 45° Skew, Cross Section Details
TRPWH 45-3-20	Parallel Wing Hdwls., 45° Skew, Wingwall Elev.
TRPWH 45-4-20	Parallel Wing Hdwls., 45° Skew, Bott. Apron Reinf.
TRPWH 45-5-20	Parallel Wing Hdwls., 45° Skew, Top Apron Reinf.
TRPWH 45-6-20	Parallel Wing Hdwls., 45° Skew, Quantity Tabulation, 12'-0" Span, Sheet 1 of 2
TRPWH 45-6-20	Parallel Wing Hdwls., 45° Skew, Quantity Tabulation, 12'-0" Span, Sheet 2 of 2
TRPWH 45-7-20	Parallel Wing Hdwls., 45° Skew, Quantity Tabulation, 10'-0" Span, Sheet 1 of 2
TRPWH 45-7-20	Parallel Wing Hdwls., 45° Skew, Quantity Tabulation, 10'-0" Span, Sheet 2 of 2
TRCBJ 1-20	Culvert Bell Joints, 10' Spans
TRCBJ 2-20	Culvert Bell Joints, 12' Spans
TRCBJ 3-20	Culvert Bell Joints, All Spans

ENGLISHLRFDSTANDARDTRIPLECULVERTS.DGN - TRRCB G1-20 - THIS SHEET ISSUED 07-2020.

LATEST REVISION DATE	 APPROVED BY BRIDGE ENGINEER		
		Standard Design Triple Reinforced Concrete Box Culverts July, 2020	
		Index of Sheets	TRRCB G1-20



Triple Reinforced Concrete Box Culvert Standards

General Notes:

- 1. The RCB culvert sections are designed for HL-93 live load and earth fills of varying heights.
- 2. Vertical earth pressure, EV=0.120 kcf.
Horizontal earth pressure, EHmax = 0.060 kcf max, EHmin = 0.030 kcf.
- 3. The RCB culvert sections are designed for Class 1 exposure conditions except:
Class 2 exposure condition is utilized for the slab design in 0' fill instances.
- 4. All slab and floor reinforcing steel is to be supported at intervals of not more than 3'-0" in either direction as outlined in the Standard Specifications.
- 5. The clear distance from face of concrete to near edge or end of reinforcing bar to be 2" unless otherwise noted.
- 6. Except for dowel bars 5r1 in slab, longitudinal reinforcing is not to extend thru the construction joints.
- 7. Floor of barrel is to be finished smooth. Sides of footing are to be formed to insure correct line and grade.
- 8. The permissible construction joint at the top of the walls may be lowered at the Contractor's option with Engineer's approval.
- 9. The reinforcement supplied for this structure shall be Grade 60 reinforcement in accordance with the Standard Specifications. The design stresses are based on ASTM A706 Grade 60 reinforcement.
- 10. The vertical bars in the walls may be spliced above the footing at the Contractor's option as follows:

Bar Size Number	4	5	6	7	8	9
Minimum Splice Length	20"	24"	29"	34"	38"	47"

This splice, if used, will be at the Contractor's expense.

- 11. Reinforcing bar clearances will be as follows:
Edge clearances: 2" except
Top of floor 2¼" to near transverse reinforcing bar
Bottom of floor 3½" to near transverse reinforcing bar
End clearances:
Vertical top 2"
Vertical bottom 3" or 3½" if overall height of the culvert is not to a full inch
Transverse 2"
12. All construction joints shall be formed with a beveled keyway except at bell joints.
- 13. All beveled keyways shall be centered.
- 14. Keyway size shall be 2"x4" except as follows:
Keyway between the floor and wall shall be 2"x6" when the wall is greater than 10 inches wide.
- 15. Keyway dimensions shown on the plans are based on nominal dimensions unless stated otherwise. In addition, the bevel used on the keyway shall be limited to a maximum of 10 degrees from vertical.
- 16. If 0' of fill is specified, details for paving notch and reference to epoxy coating of slab reinforcing steel, if applicable, shall be included in the final plans.
- 17. All dimensions are in feet and inches unless otherwise noted or shown.
- 18. See current Standard Specifications regarding concrete form removal.
- 19. These culvert standards label all reinforcing steel with English notation (5a1 is ⅝ inch diameter bar). English reinforcing steel received in the field may display the following "bar designation". The "bar designation" is the stamped impression on the reinforcing bars, and is equivalent to the bar diameter in millimeters.

English Size	4	5	6	7	8	9
Bar Designation	13	16	19	22	25	29

- 20. In the event the slab thickness at the barrel end section exceeds 18 inches, the culvert parapet shall extend a minimum of 6 inches above the top of the culvert slab. Refer to the Culvert Design Manual for instructions. These details are to be included in the design plans to address these situations.

Specifications:

Design:
AASHTO LRFD Bridge Design Specifications, 8th Ed., Series of 2017.

Construction:
Iowa Department of Transportation Standard Specifications for Highway and Bridge Construction, current series, plus applicable General Supplemental Specifications, Developmental Specifications, Supplemental Specifications and Special Provisions

Design Stresses:

Design stresses for the following materials are in accordance with the AASHTO LRFD Bridge Design Specifications, 8th Ed., Series of 2017:
Reinforcing steel in accordance with AASHTO LRFD Section 5, Grade 60.
Concrete in accordance with AASHTO LRFD Section 5, f'c = 4.0 ksi.

ENGLISHLRFDSIGNEDTRIPLECULVERTS.DGN - TRRCB G2-20 - THIS SHEET ISSUED 07-2020.


LATEST REVISION DATE


APPROVED BY BRIDGE ENGINEER



Standard Design
Triple Reinforced Concrete Box Culverts
July, 2020

General Notes & Specifications

TRRCB G2-20



ENGLISHLRFDDESIGNEDTRIPLECULVERTS.DGN - TRRCB 12-7-20 - THIS SHEET ISSUED 07-2020.



Triple 12' x 7' Barrel Section

Notes:

1. Dimensions listed on this sheet to be used in conjunction with Sheet TRRCB G3-20.
2. Fill, dimensions "S" and "H" are in feet.
3. Dimensions "A", "B", "C", "D", and "Sp." listed in the bar list are in inches.
4. Dimensions "L", "H", "V" are in feet and inches.


LATEST REVISION DATE	 APPROVED BY BRIDGE ENGINEER	 Standard Design Triple Reinforced Concrete Box Culverts July, 2020	
		Culvert Barrel Details 12' x 7' Barrel Sections	TRRCB 12-7-20 Sheet 1 of 2

ENGLISHLRFDSIGNEDTRIPLECULVERTS.DGN - TRRCB 12-7s2-20 - THIS SHEET ISSUED 07-2020.

Variable Dimensions and Quantities for Triple 12' x 7' Barrel Sections																																																									
Dimensions														Bar List																																											
														a1			a2			b1			b2			e1			e2			f1			f2			k1			k2			k3			k4					k6			k7		
Fill	S	H	A	B	C	D	E	R	O	T	U	W	X	Z	Size	Sp.	L	Size	Sp.	L	Size	Sp.	No.	Size	Sp.	No.	Size	Sp.	No.	Size	Sp.	No.	Size	Sp.	No.	Size	Sp.	L	Size	Sp.	L	Size	Sp.	L	H	V	Size	Sp.	L	Size	Sp.	L					
0	12	7	14	11.5	9	9	9	0'0	0'0	7'7	2'7	5'2	4'3	4	12	9'0	6	9	9'0	4	6	28	4	6	30	4	12	33	4	17	30	4	12	39	4	17	30	6	18	38'8	6	18	12'11	4	18	12'9	5	9	7'10	4'3	3'7	5	18	38'8	6	18	15'2
1	12	7	13	11	9	9	9	0'8	0'1	7'7	2'8	4'5	4'3	4	12	8'11	6	9	8'11	4	6	28	4	6	30	4	12	33	4	17	30	4	12	39	4	17	30	6	18	38'8	6	18	12'10	5	18	11'5	6	12	8'8	4'4	4'4	5	18	38'8	6	18	15'2
2	12	7	10	10	9	9	9	2'5	1'10	6'1	3'6	5'2	4'1	4	9	8'7	7	9	8'7	4	6	28	4	6	30	4	12	33	4	17	30	4	12	39	4	17	30	6	12	38'8	5	12	10'2	4	12	7'11	6	9	7'4	3'8	3'8	5	18	38'8	8	18	14'1
3-6	12	7	9	10.5	9	9	9	3'10	2'6	4'9	3'6	5'2	4'1	4	12	8'6	6	9	8'6	4	6	28	4	6	30	4	12	33	4	17	30	4	12	39	4	17	30	5	9	38'8	4	9	8'10	4	9	5'1	5	6	7'0	3'6	3'6	5	9	38'8	5	9	10'3
7-8	12	7	10	11.5	9	9	9	5'2	2'11	3'11	3'2	5'2	3'11	4	12	8'8	6	9	8'8	4	6	28	4	6	30	4	12	33	4	17	30	4	12	39	4	17	30	5	9	38'8	4	9	8'4	4	9	2'5	5	6	6'6	3'3	3'3	5	9	38'8	5	9	8'3
9-10	12	7	11	13	9	9	9	5'2	2'9	3'10	2'10	5'2	3'8	4	12	8'11	6	9	8'11	4	6	28	4	6	30	4	12	33	4	17	30	4	12	39	4	17	30	5	9	38'8	4	9	8'10	4	9	2'5	5	6	6'2	2'10	3'4	4	9	38'8	6	9	8'1
11-12	12	7	12	14	9	9	9	5'2	2'9	3'10	2'8	4'3	3'9	4	12	9'1	6	9	9'1	4	6	28	4	6	30	4	12	33	4	17	30	4	12	39	4	17	30	6	12	38'8	5	12	9'0	4	12	2'5	5	6	6'2	2'9	3'5	5	12	38'8	7	12	8'2
14-15	12	7	13.5	15.5	9	6	9	5'2	2'5	3'10	2'3	4'2	3'9	4	6	9'4	6	9	9'4	4	6	28	4	6	30	4	12	33	4	17	30	4	12	39	4	17	30	6	12	38'8	5	12	10'1	4	12	2'5	6	12	6'7	2'8	3'11	5	12	38'8	7	12	8'2
16-17	12	7	14.5	16.5	9	6	9	4'0	1'10	3'10	2'0	4'1	3'10	4	6	9'6	6	9	9'6	4	6	28	4	6	30	4	12	33	4	17	30	4	12	39	4	17	30	7	18	38'8	7	18	11'1	4	18	4'9	6	12	6'8	2'8	4'0	5	9	38'8	6	9	8'3
18-19	12	7	15.5	18	9	6	9	3'11	1'9	3'11	1'8	4'9	3'11	4	6	9'8	6	9	9'8	4	6	28	4	6	30	4	12	33	4	17	30	4	12	39	4	17	30	7	18	38'8	7	18	11'2	4	18	4'11	4	6	6'1	2'9	3'4	5	9	38'8	6	9	8'5
20-21	12	7	17	19	9	6	9	3'9	1'2	4'0	1'8	4'9	4'0	4	6	9'11	6	9	9'11	4	6	28	4	6	30	4	12	33	4	17	30	4	12	39	4	17	30	7	18	38'8	7	18	11'9	4	18	5'3	4	6	6'4	2'10	3'6	5	9	38'8	6	9	8'8
22-23	12	7	18	20	9	6	9	3'9	1'1	4'0	1'2	4'8	4'1	4	6	10'1	6	9	10'1	4	6	28	4	6	30	4	12	33	4	17	30	4	12	39	4	17	30	5	9	38'8	5	9	11'10	4	9	5'3	4	6	6'5	2'10	3'7	5	9	38'8	6	9	8'9
24-25	12	7	19.5	21.5	9	9	9	3'8	0'11	4'1	1'0	4'6	4'2	5	12	10'4	6	9	10'4	4	6	28	4	6	30	4	12	33	4	17	30	5	12	39	4	17	30	5	9	38'8	5	9	12'0	4	9	5'5	4	6	6'7	2'11	3'8	5	9	38'8	6	9	8'11

	Bar List																								Quantities						
	k9			m1			m2			m3			m4					m6			m7			m9			Concrete (CY/FT)			Steel	
Fill	Size	Sp.	L	Size	Sp.	L	Size	Sp.	L	Size	Sp.	L	Size	Sp.	L	H	V	Size	Sp.	L	Size	Sp.	L	Size	Sp.	L	Slab	Floor	Walls	Total	(LB/FT)
0	6	4.5	38'-8	6	18	39'-2	6	18	9'-2	4	18	2'-5	6	9	12'-8	5'-3	7'-5	4	9	39'-2	5	9	8'-7	5	4.5	39'-2	1.766	1.483	0.729	3.978	509.84
1	6	4.5	38'-8	5	12	39'-2	5	12	8'-9	4	12	3'-11	7	12	12'-3	4'-11	7'-4	4	9	39'-2	5	9	8'-6	5	4.5	39'-2	1.646	1.422	0.729	3.797	517.95
2	8	4.5	38'-8	6	12	39'-2	5	12	7'-0	4	12	2'-5	6	9	11'-0	3'-9	7'-3	4	9	39'-2	6	9	8'-4	6	4.5	39'-2	1.285	1.301	0.729	3.315	588.16
3-6	5	4.5	38'-8	6	12	39'-2	5	12	7'-1	4	12	2'-5	5	6	10'-10	3'-6	7'-4	5	12	39'-2	7	12	8'-5	7	4.5	39'-2	1.165	1.362	0.729	3.256	565.55
7-8	5	4.5	38'-8	6	12	39'-2	5	12	7'-11	4	12	2'-5	5	6	10'-6	3'-1	7'-5	5	12	39'-2	7	12	8'-1	7	4.5	39'-2	1.285	1.483	0.729	3.497	554.97
9-10	6	4.5	38'-8	6	12	39'-2	5	12	8'-10	4	12	2'-5	5	6	10'-4	2'-10	7'-6	4	9	39'-2	6	9	7'-9	6	4.5	39'-2	1.405	1.666	0.729	3.800	538.79
11-12	7	4.5	38'-8	6	12	39'-2	5	12	9'-3	4	12	4'-3	5	6	10'-4	2'-9	7'-7	4	9	39'-2	6	9	7'-11	6	4.5	39'-2	1.526	1.788	0.729	4.043	560.26
13-15	7	4.5	38'-8	5	9	39'-2	5	9	10'-6	4	9	4'-5	6	12	10'-6	2'-9	7'-9	5	12	39'-2	7	12	8'-1	7	4.5	39'-2	1.706	1.971	0.729	4.406	574.95
16-17	6	4.5	38'-8	5	9	39'-2	5	9	11'-0	4	9	4'-7	6	12	10'-7	2'-9	7'-10	5	12	39'-2	7	12	8'-3	7	4.5	39'-2	1.827	2.093	0.729	4.649	595.68
18-19	6	4.5	38'-8	5	9	39'-2	5	9	11'-4	4	9	3'-3	4	6	10'-9	2'-10	7'-11	5	12	39'-2	7	12	8'-6	7	4.5	39'-2	1.947	2.276	0.729	4.952	588.18
20-21	6	4.5	38'-8	6	12	39'-2	6	12	11'-4	4	12	3'-3	4	6	10'-10	2'-10	8'-0	5	12	39'-2	7	12	8'-8	7	4.5	39'-2	2.127	2.398	0.729	5.254	602.16
22-23	6	4.5	38'-8	6	12	39'-2	6	12	11'-10	4	12	3'-5	4	6	11'-0	2'-11	8'-1	5	9	39'-2	6	9	8'-11	6	4.5	39'-2	2.248	2.520	0.729	5.497	615.76
24-25	6	4.5	38'-8	6	12	39'-2	6	12	12'-0	4	12	3'-9	4	6	11'-3	3'-0	8'-3	5	9	39'-2	6	9	9'-1	6	4.5	39'-2	2.428	2.703	0.729	5.860	630.11

Bent Bar Detail



Note:
All dimensions are out to out.
D = pin diameter.

Notes:

- Dimensions listed on this sheet to be used in conjunction with Sheet TRRCB G3-20.
- Fill, dimensions "S" and "H" are in feet.
- Dimensions "A", "B", "C", "D", and "Sp." listed in the bar list are in inches.
- Dimensions "L", "H", "V" are in feet and inches.

LATEST REVISION DATE



APPROVED BY BRIDGE ENGINEER



Standard Design
Triple Reinforced Concrete
Box Culverts
July, 2020

Culvert Barrel
Details
12' x 7' Barrel Sections

TRRCB
12-7-20
Sheet 2 of 2



Triple Reinforced Concrete Box Culvert Standards - Flared Wing Headwalls

General Notes:

- 1. The RCB culvert sections are designed for HL-93 live load and earth fills of varying heights.
- 2. Vertical earth pressure, EV=0.120 kcf.
Horizontal earth pressure, EHmax = 0.060 kcf max, EHmin = 0.030 kcf.
- 3. The RCB culvert sections are designed for Class 1 exposure conditions except:
Class 2 exposure condition is utilized for the slab design in 0' fill instances.
- 4. All slab and floor reinforcing steel is to be supported at intervals of not more than 3'-0" in either direction as outlined in the Standard Specifications.
- 5. The clear distance from face of concrete to near edge or end of reinforcing bar to be 2" unless otherwise noted.
- 6. Except for dowel bars 5r1 in slab, longitudinal reinforcing is not to extend thru the construction joints.
- 7. Floor of barrel is to be finished smooth. Sides of footing are to be formed to ensure correct line and grade.
- 8. The permissible construction joint at the top of the walls may be lowered at the Contractor's option with Engineer's approval.
- 9. The reinforcement supplied for this structure shall be Grade 60 reinforcement in accordance with the Standard Specifications. The design stresses are based on ASTM A706 Grade 60 reinforcement.
- 10. The vertical bars in the walls may be spliced above the footing at the Contractor's option as follows:

Bar Size Number	4	5	6	7	8	9
Minimum Splice Length	20"	24"	29"	34"	38"	47"

- This splice, if used, will be at the Contractor's expense.
- 11. Reinforcing bar clearances will be as follows:
Edge clearances: 2" except
Top of floor 2¼" to near transverse reinforcing bar
Bottom of floor 3½" to near transverse reinforcing bar
End clearances:
Vertical top 2"
Vertical bottom 3" or 3½" if overall height of the culvert is not to a full inch
Transverse 2"
 - 12. All construction joints shall be formed with a beveled keyway except at bell joints.
 - 13. All beveled keyways shall be centered.
 - 14. Keyway size shall be 2"x4" except as follows:
Keyway between the floor and wall shall be 2"x6" when the wall is greater than 10 inches wide.
 - 15. Keyway dimensions shown on the plans are based on nominal dimensions unless stated otherwise. In addition, the bevel used on the keyway shall be limited to a maximum of 10 degrees from vertical.
 - 16. If 0' of fill is specified, details for paving notch and reference to epoxy coating of slab reinforcing steel, if applicable, shall be included in the final plans.
 - 17. All dimensions are in feet and inches unless otherwise noted or shown.
 - 18. Dimensions with parenthesis () indicate a reference dimension.
 - 19. See current Standard Specifications regarding concrete form removal.
 - 20. These culvert standards label all reinforcing steel with English notation (5a1 is ⅝ inch diameter bar). English reinforcing steel received in the field may display the following "bar designation". The "bar designation" is the stamped impression on the reinforcing bars, and is equivalent to the bar diameter in millimeters.

English Size	4	5	6	7	8	9
Bar Designation	13	16	19	22	25	29

- 21. In the event the slab thickness at the barrel end section exceeds 18 inches, the culvert parapet shall extend a minimum of 6 inches above the top of the culvert slab. Refer to the Culvert Design Manual for instructions. These details are to be included in the design plans to address these situations.
- 22. For barrel details used in conjunction with these flared wing headwall standards, see the Triple Reinforced Concrete Box Culvert Standards (TRRCB).

Index for Triple Culvert Standards:

TRFWH G1-21	Index & General Notes
TRFWH 0-1-21	Flared Wing Hdwls., 0° Skew, Dimension Plan & Table
TRFWH 0-2-21	Flared Wing Hdwls., 0° Skew, Apron Details
TRFWH 0-3-21	Flared Wing Hdwls., 0° Skew, Parapet & Curtain Wall Details
TRFWH 0-4-21	Flared Wing Hdwls., 0° Skew, Wingwall Details
TRFWH 0-5-21	Flared Wing Hdwls., 0° Skew, Quantity Tabulation, 12'-0" Span, Sheet 1 of 2
TRFWH 0-5-21	Flared Wing Hdwls., 0° Skew, Quantity Tabulation, 12'-0" Span, Sheet 2 of 2
TRFWH 0-6-21	Flared Wing Hdwls., 0° Skew, Quantity Tabulation, 10'-0" Span, Sheet 1 of 2
TRFWH 0-6-21	Flared Wing Hdwls., 0° Skew, Quantity Tabulation, 10'-0" Span, Sheet 2 of 2
TRFWH 15-1-21	Flared Wing Hdwls., 15° Skew, Dimension Plan
TRFWH 15-2-21	Flared Wing Hdwls., 15° Skew, Dimension Table
TRFWH 15-3-21	Flared Wing Hdwls., 15° Skew, Top Apron Detail
TRFWH 15-4-21	Flared Wing Hdwls., 15° Skew, Bottom Apron Detail
TRFWH 15-5-21	Flared Wing Hdwls., 15° Skew, Parapet & Curtain Wall Details
TRFWH 15-6-21	Flared Wing Hdwls., 15° Skew, Wingwall Details
TRFWH 15-7-21	Flared Wing Hdwls., 15° Skew, Quantity Tabulation, 12'-0" Span, Sheet 1 of 2
TRFWH 15-7-21	Flared Wing Hdwls., 15° Skew, Quantity Tabulation, 12'-0" Span, Sheet 2 of 2
TRFWH 15-8-21	Flared Wing Hdwls., 15° Skew, Quantity Tabulation, 10'-0" Span, Sheet 1 of 2
TRFWH 15-8-21	Flared Wing Hdwls., 15° Skew, Quantity Tabulation, 10'-0" Span, Sheet 2 of 2
TRFWH 30-1-21	Flared Wing Hdwls., 30° Skew, Dimension Plan
TRFWH 30-2-21	Flared Wing Hdwls., 30° Skew, Dimension Table
TRFWH 30-3-21	Flared Wing Hdwls., 30° Skew, Top Apron Detail
TRFWH 30-4-21	Flared Wing Hdwls., 30° Skew, Bottom Apron Detail
TRFWH 30-5-21	Flared Wing Hdwls., 30° Skew, Parapet & Curtain Wall Details
TRFWH 30-6-21	Flared Wing Hdwls., 30° Skew, Wingwall Details
TRFWH 30-7-21	Flared Wing Hdwls., 30° Skew, Quantity Tabulation, 12'-0" Span, Sheet 1 of 2
TRFWH 30-7-21	Flared Wing Hdwls., 30° Skew, Quantity Tabulation, 12'-0" Span, Sheet 2 of 2
TRFWH 30-8-21	Flared Wing Hdwls., 30° Skew, Quantity Tabulation, 10'-0" Span, Sheet 1 of 2
TRFWH 30-8-21	Flared Wing Hdwls., 30° Skew, Quantity Tabulation, 10'-0" Span, Sheet 2 of 2
TRFWH 45-1-21	Flared Wing Hdwls., 45° Skew, Dimension Plan
TRFWH 45-2-21	Flared Wing Hdwls., 45° Skew, Dimension Table
TRFWH 45-3-21	Flared Wing Hdwls., 45° Skew, Top Apron Detail
TRFWH 45-4-21	Flared Wing Hdwls., 45° Skew, Bottom Apron Detail
TRFWH 45-5-21	Flared Wing Hdwls., 45° Skew, Parapet & Curtain Wall Details
TRFWH 45-6-21	Flared Wing Hdwls., 45° Skew, Wingwall Details
TRFWH 45-7-21	Flared Wing Hdwls., 45° Skew, Quantity Tabulation, 12'-0" Span, Sheet 1 of 2
TRFWH 45-7-21	Flared Wing Hdwls., 45° Skew, Quantity Tabulation, 12'-0" Span, Sheet 2 of 2
TRFWH 45-8-21	Flared Wing Hdwls., 45° Skew, Quantity Tabulation, 10'-0" Span, Sheet 1 of 2
TRFWH 45-8-21	Flared Wing Hdwls., 45° Skew, Quantity Tabulation, 10'-0" Span, Sheet 2 of 2

Specifications:

Design:
AASHTO LRFD Bridge Design Specifications, 8th Ed., Series of 2017.

Construction:
Iowa Department of Transportation Standard Specifications for Highway and Bridge Construction, current series, plus applicable General Supplemental Specifications, Developmental Specifications, Supplemental Specifications and Special Provisions

Design Stresses:

Design stresses for the following materials are in accordance with the AASHTO LRFD Bridge Design Specifications, 8th Ed., Series of 2017:
Reinforcing steel in accordance with AASHTO LRFD Section 5, Grade 60.
Concrete in accordance with AASHTO LRFD Section 5, f'c = 4.0 ksi.

LATEST REVISION DATE	 APPROVED BY BRIDGE ENGINEER	 Standard Design - Triple Reinforced Concrete Box Culverts	
		Flared Wing Headwalls February, 2021	
		Index of Sheets, General Notes & Specifications	TRFWH G1-21