



**SPECIAL PROVISIONS
FOR
TACTILE DIRECTIONAL INDICATOR**

**Linn County
TAP-U-1187(801)--8I-57**

**Effective Date
August 18, 2026**

THE STANDARD SPECIFICATIONS, SERIES 2023, ARE AMENDED BY THE FOLLOWING MODIFICATIONS AND ADDITIONS. THESE ARE SPECIAL PROVISIONS AND THEY SHALL PREVAIL OVER THOSE PUBLISHED IN THE STANDARD SPECIFICATIONS.

236079.01 DESCRIPTION.

A. General.

This item involves supplying and installing the tactile directional indicator as shown on the contract documents and referenced within the following specifications.

B. Specification References.

1. TufTile - ADA Detectable Warning Products, or approved equal.
2. ADA Solutions.

C. Submittals.

1. Material and Equipment List.

Within 30 days after awarding of the contract for the project, submit a completed list of materials and equipment. Submit two copies to the Engineer for written approval before any equipment or materials are ordered.

2. Shop Drawings.

Submit three copies of shop drawings for the tactile directional indicator to be furnished on the project. Submit three copies of catalog cuts and manufacturer's specifications for all items in the equipment list.

236079.02 MATERIALS.

- A.** The tactile directional indicators shall be cast iron, and brick red (Federal # 22144 or equivalent) in color.
- B.** Provide manufactured tactile directional indicators with a non-slip surface, that meets the

requirements of the tactile directional indicator detail shown on the plans

236079.03 CONSTRUCTION.

- A. Wet – Set.
- B. Place directional guidance tile into concrete until the top surface is flush. A stringline is recommended to maintain a straight installation. Indicators shall be placed at the top of the bike ramp, in front of the grade break, as shown in the plans.
- C. Using a rubber mallet, tap the entire surface of the tile to ensure proper consolidation of concrete around the anchors.
- D. Finish concrete to require specifications. Do not stand or walk on tile until concrete is fully cured.
- E. Once all post installation finishing has been completed, clean any excess concrete slurry that may have consolidated on the top surface.

236079.04 METHOD OF MEASUREMENT.

Measurement shall be at the contract unit price per linear foot for tactile directional indicator.

236079.05 BASIS OF PAYMENT.

- A. This item will be paid at the contract unit price per linear foot for tactile directional indicator installed. All labor, materials, and equipment necessary for installation of the inline drain will not be paid for separately, but shall be considered incidental to this item.
- B. Unit price includes, but is not limited to, the furnishing and installation of all labor, materials, equipment, bolts, connectors, screws, tiles and all other parts required as detailed on the tactile directional indicator detail shall be considered incidental to this item. This item includes all surface preparation work, repair or restoration of concrete pavement to pre-construction conditions.