

EPOXY COATED REINFORCING BAR LIST, PRECAST ABUTMENT BACKWALL (0° SKEW, ONE UNIT)

(INCLUDED IN BID ITEM "PRECAST ABUTMENT BACKWALL (CONCRETE WINGS)", EACH)

BAR	LOCATION	SPAN	REINFORCED CONCRETE BOX BEAMS												PRETENSIONED PRESTRESSED CONCRETE BOX BEAMS											
			30'-0"			40'-0"			50'-0"			30'-0"			40'-0"			50'-0"			60'-0"			70'-0"		
			SHAPE	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	
4d1	BACKWALL, VERTICAL STIRRUPS		14	6'-1"	57	14	6'-1"	57	14	7'-1"	66	14	5'-1"	48	14	5'-1"	48	14	6'-1"	57	14	6'-1"	57	14	7'-1"	66
4d2	BACKWALL, VERTICAL STIRRUPS		1	9'-9"	7	1	9'-9"	7	1	10'-9"	7	1	8'-9"	6	1	8'-9"	6	1	9'-9"	7	1	9'-9"	7	1	10'-9"	7
4d3	BACKWALL, VERTICAL STIRRUPS		1	8'-9"	6	1	8'-9"	6	1	9'-9"	7	1	8'-1"	5	1	8'-1"	5	1	8'-9"	6	1	8'-9"	6	1	9'-9"	7
4d4	BACKWALL, VERTICAL STIRRUPS		1	7'-11"	5	1	7'-11"	5	1	8'-11"	6	1	7'-7"	5	1	7'-7"	5	1	7'-11"	5	1	7'-11"	5	1	8'-11"	6
4d5	BACKWALL, VERTICAL STIRRUPS		1	6'-11"	5	1	6'-11"	5	1	7'-11"	5	1	6'-11"	5	1	6'-11"	5	1	6'-11"	5	1	6'-11"	5	1	7'-11"	5
8d7 *	BACKWALL, VERTICAL		7	2'-2"	40	7	2'-2"	40	7	2'-8"	50	7	1'-8"	31	7	1'-8"	31	7	2'-2"	40	7	2'-2"	40	7	2'-8"	50
6g1	BACKWALL, HORIZONTAL		2	19'-7"	59	2	19'-7"	59	2	20'-1"	60	2	18'-6"	56	2	18'-6"	56	2	19'-7"	59	2	19'-7"	59	2	20'-1"	60
6g2	BACKWALL, HORIZONTAL		2	15'-3"	46	2	15'-3"	46	2	15'-9"	47	2	14'-9"	44	2	14'-9"	44	2	15'-3"	46	2	15'-3"	46	2	15'-9"	47
6g3	BACKWALL, HORIZONTAL		2	17'-3"	52	2	17'-3"	52	2	17'-3"	52	2	16'-3"	49	2	16'-3"	49	2	17'-3"	52	2	17'-3"	52	2	17'-3"	52
6g4	BACKWALL, HORIZONTAL		4	3'-7"	22	4	3'-7"	22	4	3'-7"	22	4	2'-7"	16	4	2'-7"	16	4	3'-7"	22	4	3'-7"	22	4	3'-7"	22
TOTAL (LBS.)			299			299			322			265			265			299			299			322		

* SEE BENT BAR DETAILS. THE LENGTHS SHOWN DO NOT INCLUDE AN ALLOWANCE FOR THE THREADED END. BAR LENGTHS MAY NEED TO INCREASE DEPENDING ON THE MECHANICAL COUPLER ASSEMBLY USED. THE COST OF THE THREADED PORTION OF THESE BARS IS TO BE INCLUDED IN THE PRICE BID FOR THE BACKWALLS. THE WEIGHT OF THE THREADED END IS NOT INCLUDED IN THE QUANTITY SHOWN.

ABUTMENT NOTES:

MINIMUM CLEAR DISTANCE FROM FACE OF CONCRETE TO NEAR REINFORCING BAR IS TO BE 2" UNLESS OTHERWISE NOTED OR SHOWN. ABUTMENT PILES SHALL BE DRIVEN TO VALUES SHOWN IN THE DESIGN PLANS. THE BACKWALL SHALL BE PLACED AFTER THE UHPC JOINTS BETWEEN THE BEAMS HAVE BEEN COMPLETED. MECHANICAL COUPLERS SHALL BE EPOXY COATED. THE MECHANICAL COUPLERS SHALL MEET THE REQUIREMENTS OF MATERIALS IM 451 APPENDIX E, EXCEPT THE MECHANICAL SPLICE IS REQUIRED TO BE EMBEDDED ON THE ABUTMENT FOOTING SIDE OF THE CONSTRUCTION JOINT. THE PRECAST BACKWALLS SHALL BE DRY FITTED TO THE PRECAST ABUTMENTS IN THE PRECASTER'S YARD OR SHOP BEFORE SHIPPING THE PIECES TO THE FIELD. THE ENGINEER SHALL HAVE 48 HOURS NOTICE TO VIEW AND APPROVE THE CONNECTED PRECAST PIECES BEFORE THEY ARE SHIPPED TO THE FIELD.

EPOXY COATED REINFORCING BAR LIST, PRECAST ABUTMENT FOOTING (ONE FOOTING)

(INCLUDED IN BID ITEM "PRECAST FOOTING (CONCRETE WINGS)", EACH)

BAR	LOCATION	SPAN	REINFORCED CONCRETE BOX BEAMS												PRETENSIONED PRESTRESSED CONCRETE BOX BEAMS											
			30'-0"			40'-0"			50'-0"			30'-0"			40'-0"			50'-0"			60'-0"			70'-0"		
			SHAPE	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	NO.	WEIGHT	
5c1	FOOTING END, VERTICAL		8	3'-9"	31	8	3'-9"	31	8	3'-9"	31	8	3'-9"	31	8	3'-9"	31	8	3'-9"	31	8	3'-9"	31	8	3'-9"	31
5c2	FOOTING END, HORIZONTAL		8	4'-4"	36	8	4'-4"	36	8	4'-4"	36	8	4'-4"	36	8	4'-4"	36	8	4'-4"	36	8	4'-4"	36	8	4'-4"	36
8d6**	FOOTING, VERTICAL		14	2'-7"	97	14	2'-7"	97	14	2'-7"	97	14	2'-7"	97	14	2'-7"	97	14	2'-7"	97	14	2'-7"	97	14	2'-7"	97
8f1	FOOTING, LONGITUDINAL		12	27'-0"	865	12	27'-0"	865	12	27'-0"	865	12	27'-0"	865	12	27'-0"	865	12	27'-0"	865	12	27'-0"	865	12	27'-0"	865
6f2	FOOTING, LONGITUDINAL		8	3'-7"	43	8	3'-7"	43	8	3'-7"	43	8	3'-7"	43	8	3'-7"	43	8	3'-7"	43	10	2'-5"	36			
5p1	FOOTING, HOOPS		52	11'-8"	633	52	11'-8"	633	52	11'-8"	633	52	11'-8"	633	52	11'-8"	633	52	11'-8"	633	52	11'-8"	633	52	11'-8"	633
	1 1/2" DIA. SMOOTH DOWELS		6	2'-9"	69	6	2'-9"	69	6	3'-3"	82	6	2'-3"	56	6	2'-3"	56	6	2'-9"	69	6	2'-9"	69	6	3'-3"	82
TOTAL (LBS.)			1,774			1,774			1,787			1,761			1,761			1,774			1,774			1,780		

** INCLUDES MECHANICAL COUPLERS. SEE BENT BAR DETAILS.

CMP PILE


POCKET NOTE:

PILE POCKETS SHALL CONSIST OF GALVANIZED STEEL CORRUGATED METAL PIPE (CMP), TYPE 1, 16 GAGE, IN ACCORDANCE WITH THE PRECAST CONCRETE ELEMENTS NOTES. CMP FOR INDIVIDUAL POCKETS SHALL CONSIST OF A SINGLE LENGTH OF PIPE. SPLICING OF PIPE SECTIONS SHALL NOT BE ALLOWED. NOMINAL CMP SIZE SHALL BE 21". FOLLOWING SETTING OF THE FOOTING, THE PILE POCKETS SHALL BE FILLED LEVEL WITH THE TOP OF FOOTING USING HIGH EARLY STRENGTH SELF-CONSOLIDATING CONCRETE IN ACCORDANCE WITH THE PRECAST CONCRETE ELEMENTS NOTES.

BACKWALL SETTING NOTES:

THE 8d7 BARS SHALL BE SET AS DOWELS IN PREFORMED HOLES. THE DOWELS SHALL BE INSTALLED IN ACCORDANCE WITH THE GROUT MANUFACTURER'S RECOMMENDATIONS. A POLYMER GROUT SYSTEM IN ACCORDANCE WITH STANDARD SPECIFICATIONS SHALL BE USED AS A BONDING AGENT FOR VERTICAL DOWELS. SET PRECAST BACKWALLS ON AN EPOXY GROUT BED TO HELP LEVEL AND CONNECT THE PRECAST ELEMENTS. FOLLOW ALL MANUFACTURER'S RECOMMENDATIONS FOR INSTALLATION.

BACKWALL BENT BAR DETAILS




4d1, 4d2, 4d3, 4d4 & 4d5

6g1

8d7 *

FOOTING BENT BAR DETAILS



5c1 & 5c2

5p1

8d6 **

NOTE: ALL DIMENSIONS ARE OUT TO OUT. D= PIN DIAMETER.

PRECAST CONCRETE QUANTITIES (INCLUDED IN PRECAST UNITS, (CONCRETE WINGS))


LOCATION	SPAN	REINFORCED CONCRETE BOX BEAMS			PRETENSIONED PRESTRESSED CONCRETE BOX BEAMS				
		30'-0"	40'-0"	50'-0"	30'-0"	40'-0"	50'-0"	60'-0"	70'-0"
EACH BACKWALL UNIT (C.Y.) *		1.7	1.7	2.0	1.3	1.3	1.7	1.7	2.0
EACH FOOTING (C.Y.)		9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.4
CMP PILE POCKETS (EACH FOOTING) (C.Y.) **		1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.7

* INCLUDES THE COST OF FURNISHING AND PLACING ALL PREFORMED EXPANSION JOINT FILLER.
** HIGH EARLY STRENGTH SELF-CONSOLIDATING CONCRETE.

BAR	DIM.	REINFORCED CONCRETE BOX BEAMS			PRETENSIONED PRESTRESSED CONCRETE BOX BEAMS				
		30'-0"	40'-0"	50'-0"	30'-0"	40'-0"	50'-0"	60'-0"	70'-0"
6g1	"A"	3'-9"	3'-9"	3'-9"	2'-9"	2'-9"	3'-9"	3'-9"	3'-9"
6g1	"B"	1'-10 1/2"	1'-10 1/2"	1'-10 1/2"	1'-4 1/2"	1'-4 1/2"	1'-10 1/2"	1'-10 1/2"	1'-10 1/2"
6g1	"D"	4'-2"	4'-2"	4'-2"	3'-1"	3'-1"	4'-2"	4'-2"	4'-2"
6g1	"D"	2'-0"	2'-0"	2'-6"	2'-0"	2'-0"	2'-0"	2'-0"	2'-6"
4d1	"E"	2'-0"	2'-0"	2'-6"	1'-6"	1'-6"	2'-0"	2'-0"	2'-6"
4d2	"E"	3'-10"	3'-10"	4'-4"	3'-4"	3'-4"	3'-10"	3'-10"	4'-4"
4d3	"E"	3'-4"	3'-4"	3'-10"	3'-0"	3'-0"	3'-4"	3'-4"	3'-10"
4d4	"E"	2'-11"	2'-11"	3'-5"	2'-9"	2'-9"	2'-11"	2'-11"	3'-5"
4d5	"E"	2'-5"	2'-5"	2'-11"	2'-5"	2'-5"	2'-5"	2'-5"	2'-11"

NOTE: ALL DIMENSIONS ARE OUT TO OUT. D= PIN DIAMETER.

LATEST REVISION DATE


 APPROVED BY BRIDGE ENGINEER

IOWA DOT Highway Division

STANDARD DESIGN - 24'-0" ROADWAY, SINGLE SPAN
CONCRETE BOX BEAM BRIDGES

DECEMBER, 2016

**ABUTMENT DETAILS (PRECAST)
CONCRETE WINGS
QUANTITIES
0° SKEW**

B24-20-16