


REVISED 10-11 - THE DRAIN EXTENSION BELOW THE BEAM WAS EXTENDED TO A 1'-0" DISTANCE. THE DATA FOR ONE DRAIN QUANTITIES WERE ADJUSTED FOR THE ADDITIONAL DRAIN LENGTH.




℄-℄ ABUT. BRG. "L"	A ABUT.	B	C PIER	D	E PIER	F	G ABUT.
138'-10"	1	8	1 1/2	8	1 1/2	8	1
151'-4"	2	8	1 1/2	8	1 1/2	8	2
163'-10"	2	8	1 1/2	8	1 1/2	8	2
176'-4"	2	8	1 1/2	8	1 1/2	8	2
188'-10"	2	8	1 1/2	8	1 1/2	8	2
201'-4"	2	8	1 1/2	8	1 1/2	8	2
213'-10"	2	8	1 1/2	8	1 1/2	8	2
226'-4"	2	8	1 1/2	8	1 1/2	8	2
243'-0"	2	8	1 1/2	8	1 1/2	8	2

LENGTH OF VERTICAL CURVE REQUIRED = $(20,000 \times G1 - G2)$
M.O. = $\frac{(G1 - G2) \times \text{LENGTH OF V.C.}}{8}$

(G1-G2) IS THE ALGEBRAIC DIFFERENCE OF THE APPROACH GRADES EXPRESSED IN DECIMAL FORM. G1 NEED NOT HAVE THE SAME VALUE AS G2. MAXIMUM VALUE OF G1 OR G2 IS 5%. LENGTH OF CURVE AND M.O. ARE IN FEET.


SLAB AND HAUNCH THICKNESS AT BEAMS FOR VERTICAL CURVE



℄-℄ ABUT. BRG. "L"	A ABUT.	B	C PIER	D	E PIER	F	G ABUT.
138'-10"	1	2	1 1/2	8	1 1/2	2	1
151'-4"	2	8	1 1/2	8	1 1/2	8	2
163'-10"	2	8	1 1/2	8	1 1/2	8	2
176'-4"	2	8	1 1/2	8	1 1/2	8	2
188'-10"	2	8	1 1/2	8	1 1/2	8	2
201'-4"	2	8	1 1/2	8	1 1/2	8	2
213'-10"	2	8	1 1/2	8	1 1/2	8	2
226'-4"	2	8	1 1/2	8	1 1/2	8	2
243'-0"	2	8	1 1/2	8	1 1/2	8	2

G1 MAY HAVE A + OR - SIGN. THE MINIMUM NUMERICAL VALUE OF THE GRADE IS 0.3% AND THE MAXIMUM VALUE IS 5%.


SLAB AND HAUNCH THICKNESS AT BEAMS FOR STRAIGHT GRADE




CONCRETE SEALER LIMITS FOR OPEN RAILS

CONCRETE SEALER SHALL BE APPLIED TO BOTH SIDES OF BRIDGE SLAB ON THE TOP, EDGE OF SLAB AND UNDER THE SLAB. THE CONCRETE SEALER SHALL ALSO BE APPLIED TO THE OPEN RAIL ON THE TOP, TRAFFIC FACE SIDE, BOTTOM OF RAIL, AND ON ALL SIDES OF THE OPEN RAIL POSTS.


THE CONCRETE SEALER LIMITS ARE SHOWN IN THE DETAIL AND SHALL APPLY TO THE FULL LENGTH OF BRIDGE. CONCRETE SEALER SHALL BE APPLIED IN ACCORDANCE WITH ARTICLE 2403.03, P. 3, OF THE STANDARD SPECIFICATIONS.



EXTERIOR BEAMS & OPEN RAIL




INTERIOR BEAMS



EXTERIOR BEAMS & BARRIER RAIL


TYPICAL SLAB AND HAUNCH DETAIL

* FOR SLAB THICKNESS OVER BEAMS SEE * SLAB THICKNESS DETAILS * ON THIS SHEET.




SLAB THICKNESS DETAILS

NOTE: THE SLAB THICKNESS (T) AT THE BEAMS, (8" SLAB PLUS HAUNCH) IS BASED ON THE ANTICIPATED BEAM CAMBER REMAINING AFTER PLACING THE SLAB, BUT IS NOT GUARANTEED FOR CONSTRUCTION. IF BEAM IS UNDER CAMBERED INCREASE THE HAUNCH THICKNESS OVER THE BEAM AT THE MIDPOINT OF THE SPANS (POINTS B, D AND F). IF THE BEAM IS OVER CAMBERED DECREASE THE HAUNCH THICKNESS OVER THE BEAM AT THE MIDPOINT OF THE SPANS (POINTS B, D AND F) TO A MAXIMUM OF 1/2" EMBEDMENT IN THE SLAB. IF MORE THAN 1/2" EMBEDMENT IS REQUIRED OR IF THE HAUNCH EXCEEDS 2 1/2" THE GRADE LINE IS TO BE REVISED.



SITUATION SKETCH (SHOWING DRAIN LOCATIONS)



DRAIN DETAILS

USE FOR BARRIER RAIL ONLY. NOT REQUIRED FOR OPEN RAIL.

NOTE: DRAINS ARE TO BE GALVANIZED AFTER FABRICATION. SEE "SITUATION SKETCH" FOR LOCATION OF DRAINS. WEIGHT OF DRAINS IS INCLUDED IN THE QUANTITY FOR "STRUCTURAL STEEL". WEIGHT IS BASED ON ROLLED TUBE.

DATA FOR ONE DRAIN

BEAM SIZE	A	B	C
WT. LBS.	85	96	106
LENGTH FT.	4'-4 1/2"	4'-11 1/2"	5'-5 1/2"

LATEST REVISION DATE

10-11
 Approved by Bridge Engineer
Norman E. Mc Donnell

STANDARD DESIGN - 40' ROADWAY, THREE SPAN BRIDGE

PRETENSIONED PRESTRESSED CONCRETE BEAM BRIDGES

AUGUST, 2009

SUPERSTRUCTURE DETAILS
H40-04-06